SWIFT **NEW** PRODUCT SPOTLIGHT Swift







SNAP²IT connectors

Get more done, solve jobsite challenges, meet code requirements and enhance safety

Product Description

Zinc die-cast, 1/2" Knockout MC cable connector snaps quickly on to the conduit with internal spring steel clip and then snaps into knockout with an external spring steel clip no tools required. Concrete tight when taped. Has Rectangular End stop and provided with insulated throat.

TOP PRODUCT FEATURES

- Fits widest range and variety of MC cable 14/2 to 3/3 AC, MC, HCF, MC continuous corrugated aluminum cable and MCI-A cables (steel and aluminum)...including the new MC-PCS cable that combines power and low voltage in the same MC cable ANY Snap2It Connectors LISTED for MC cable are also LISTED for MC-PCS cable! These products offer the greatest timesavings.
- Fast, secure snap-on installation
- Easy to remove, reusable connector From cable Loosen screw on top. Remove connector from cable. From box Slip screwdriver under notch in Snap-Tite® ring. Twist. Remove connector.

Dimensions



| | CATALOG NUMBER | DESCRIPTION Snap2lt® connectors | CABLE OUTSIDE DIA (OD) |
|------|-------------------|--|---------------------------|
| | 4010AST | Snap in, 1/2" KO w insulated throat | .405 to .610 |
| | 5010AST | Snap in, 1/2" KO w insulated throat | .580 to .780 |
| | 505010AST | Duplex Snap in, 3/4" KO w insulated throat | (2) .590 to .820 |
| | 4110ST | Snap in, 1/2" KO | .525 to .705 |
| | 414110ST | Duplex Snap in, 1/2" KO | (2) .525 to .640 |
| NEW! | 4141107ST | Duplex Snap in, 3/4" KO | (2) .525 to .690 |

SWIFT **NEW** PRODUCT SPOTLIGHT Swift





FLOOR BOXES

Reversible Leveling Ring • Six Conduit Hubs • Options for Divider Position

Product Description and Features

Arlington's FLOOR BOXES, COVER KITS, and accessories FOR NEW **CONCRETE** are the low cost, convenient way to install a receptacle flush with a new floor.

Made of heavy-duty plastic, our FLBC4502 4.5" non-metallic concrete **floor box** has more: SIX conduit hubs and FOUR plugs and THREE options for positioning the low voltage divider in the box.

The NEW FLBC4502LR **leveling ring** makes installing a cover easy on ANY 4.5" concrete box including our FLBC4500 and the new FLBC4502. It's REVERSIBLE! **Side A** fits any 6" round cover with a 3-1/2" screw hole pattern. Side B has a second set of holes that fits 6" covers with a 3-3/8" screw hole pattern.



Arlington®

OUTDOOR RATED NON-METALLIC ENCLOSURES

Made of heavy-duty, non-metallic UV-rated material.

Features and Benefits

- Meets NEMA 3R requirements for outdoor use when mounted with hinge on top
- Optional cam lock (sold separately)
- Non-metallic, handy 1/2" and 3/4" knockouts on top and bottom of enclosure box
- Available in gray and black